

MODEL: IGNITE POWER IPC-50



50 kVA / 40 kW
POWERED BY CUMMINS

DIESEL GENERATING SET 400/230V, 380/220V - 50 Hz

MODEL		IGNITE POWER IPC-50	
Power Pf. 0.8	Standby	kVA	55
		kW	44
	Prime	kVA	50
		kW	40

- High quality, reliable and complete power unit
- Compact design
- Easy start and maintenance possibility
- Every generating set is subject to a comprehensive test program which includes full load testing, checking and provision of all control and safety shut down functions testing
- Fully engineered with a wide range of options and accessories: Canopy, sound proof canopy and on - road trailer



ENGINE

Cummins		
Model	4BTA3.9-G2	
Engine Power Output at rated rpm	kWm	58.0
	HP	78.0
Aspiration and Cooling	Turbocharged	
Total Displacement	Litre	3.3
No. of Cylinders and Build	4 - Vertical Inline	
Engine Speed	rpm	1500
Bore and Stroke	mmxmm	102 x 120
Compression Ratio	17.3:1	
Governor	Mechanical	
Fuel Consumption at full load	L/hr	15
Fuel Tank Capacity	Litre	8 Hours
Oil Capacity	Litre	10.9
Coolant Capacity	Litre	8.3
Heat Rejection to Coolant	kW	29.1
Air Intake – Engine	litre/sec	55
Exhaust Gas Flow	litre/sec	149

- Cummins diesel engine
- Four stroke, water, cooled, turbo charged
- Direct injection fuel system
- Mechanical Governor system
- 12/24 V D.C. starter motor
- Replaceable fuel filter, oil filter and dry element air filter

- Cooling radiator and fan
- Starter battery including Rack and Cables
- Flexible fuel connection hoses and manual oil sump drain valve
- Industrial capacity exhaust silencer and steel bellows
- Jacket water heater(at automatic models) Optional
- Operation manuals and circuit diagram documents

ALTERNATOR



Design	Brushless single bearing, revolving field
Stator	2/3 pitch
Rotor	Single bearing, flexible disc
Insulation System	Class H
Standard Temperature Rise	125 - 163°C Continuous
Exciter Type	Self Excited
Phase Rotation	Clockwise
Alternator Cooling	Direct drive centrifugal blower fan
AC Waveform Total Harmonic Distortion	No load < 3.5%. Non distorting balanced linear load < 5%
Telephone Influence Factor (TIF)	<50
Telephone Harmonic Factor (THF)	<2%

- Brushless, single bearing system, flexible disc, 4 poles
- Insulation class H
- Standard degree of protection IP23
- Self-exciting and self-regulating

- Impregnation with tropicalised epoxy varnish
- Solid state Automatic Voltage Regulator
- Stator winding with 2/3 pitch for improved harmonics

CONTROL SYSTEM

Control supervision and protection panel is mounted on the genset base frame. The control panel varies depending on requirement, in general Ignite Power generators are equipped with Deep Sea **Deep Sea UK DSE4520**. The main features for Deep Sea are as follows:

KEY BENEFITS

- Hours counter provides accurate information for monitoring and maintenance periods
- User-friendly set-up and button layout for ease of use
- Multiple parameters are monitored simultaneously which are clearly displayed on a large back-lit icon display
- The module can be configured to suit a wide range of applications
- Compatible with a wide range of CAN engines, including tier 4 engine support
- Uses DSE Configuration Suite PC Software for simplified configuration
- Licence-free PC software
- IP65 rating (with optional gasket) offers increased resistance to water ingress

KEY FEATURES

- Large back-lit icon display
- Heated display option available
- Fully configurable via the fascia or PC using USB communication
- Efficient power save mode
- 3 phase generator sensing
- 3 phase mains (utility) sensing (DSE6620 only)
- Generator/load power monitoring (kW, kV A, kV Ar, pf)
- Generator overload protection
- Generator/load current monitoring and protection
- Breaker control via fascia buttons
- Fuel and start outputs (configurable when using CAN)
- 4 configurable DC outputs
- 4 configurable analogue/digital inputs
- 6 configurable digital inputs
- Configurable staged loading outputs

- CAN, MPU and alternator speed sensing in one variant
- 3 engine maintenance alarms
- Engine speed protection
- Engine hours counter
- Engine pre-heat
- Engine run-time scheduler
- Engine idle control for starting & stopping
- Fuel pump control
- Real time clock
- options available
- Battery voltage monitoring
- Start on low battery voltage
- Configurable remote start input
- 1 alternative configuration
- Comprehensive warning, electrical trip or shutdown protection upon fault condition
- LCD and LED alarm indication
- Configurable event log (50)



Also Gensets can be equipped with different control panels depending on usage such as:
 DSE 6610: Basic Autostart operation with stand alone application
 DSE 7310: advanced Autostart operation with high protections
 DSE 7320: advanced auto mains failure operation with high protection
 DSE 8610: for synchronization application/solution

OPTIONAL EQUIPMENTS

Diesel Engine

- Oil heater

Alternator

- 3/4 Pole Output Circuit Breaker
- Anti - condensation Heater

Panel

- Charge ammeter
- Transfer Switch 3 Pole
- Transfer Switch 4 Pole
- Earth Fault, single set

Accessories

- Bulk fuel tank
- Automatic filling system
- Fuel - water separator filter
- Low fuel level alarm
- Residential silencer
- Enclosure or sound proof canopy
- Trailer
- Manual oil drain pump
- Tool kit for maintenance