

MODEL: IGNITE POWER IP-400



400 kVA / 320 kW  
POWERED BY PERKINS

### DIESEL GENERATING SET 400/230V, 50 Hz, 1500RPM

MODEL		IGNITE POWER IP-400	
Power Pf. 0.8	Standby	kVA	440
		kW	360
	Prime	kVA	400
		kW	320

- High quality, reliable and complete power unit
- Compact design
- Easy start and maintenance possibility
- Every generating set is subject to a comprehensive test program which includes full load testing, checking and provision of all control and safety shut down functions testing
- Fully engineered with a wide range of options and accessories: Canopy, sound proof canopy and on - road trailer



### ENGINE

#### Perkins

Model		2206C-E13TAG3
Engine Power Output at rated rpm	kWm	368
	HP	493
Aspiration and Cooling		Turbocharged and Air to Air charged cool
Total Displacement	Litre	12.5
No. of Cylinders and Build		6 - Vertical Inline
Engine Speed	rpm	1500
Bore and Stroke	mmxmm	130 x 157
Compression Ratio		16.3:1
Governor		Electronic
Fuel Consumption at full load	L/hr	85.0
Fuel Tank Capacity	Litre	8 Hours
Oil Capacity	Litre	40.0
Coolant Capacity	Litre	51.4
Radiator Cooling Air	m <sup>3</sup> /min	654
Air Intake – Engine	m <sup>3</sup> /min	24.3
Exhaust Gas Flow	m <sup>3</sup> /min	64.6

- Heavy duty Perkins diesel engine
- Four stroke, water, cooled, turbo charged
- Direct injection fuel system
- Electronic Governor system
- 12/24 V D.C. starter and charge alternator
- Replaceable fuel filter, oil filter and dry element air filter

- Cooling radiator and fan
- Starter battery including Rack and Cables
- Flexible fuel connection hoses and manual oil sump drain valve
- Industrial capacity exhaust silencer and steel bellows
- Jacket water heater(at automatic models) Optional
- Operation manuals and circuit diagram documents

### ALTERNATOR



Design	Brushless single bearing, revolving field
Stator	2/3 pitch
Rotor	Single bearing, flexible disc
Insulation System	Class H
Standard Temperature Rise	125 - 163°C Continuous
Exciter Type	Self Excited
Phase Rotation	Clockwise
Alternator Cooling	Direct drive centrifugal blower fan
AC Waveform Total Harmonic Distortion	No load < 3.5%. Non distorting balanced linear load < 5%
Telephone Influence Factor (TIF)	<50
Telephone Harmonic Factor (THF)	<2%

- Brushless, single bearing system, flexible disc, 4 poles
- Insulation class H
- Standard degree of protection IP23
- Self-exciting and self-regulating

- Impregnation with tropicalised epoxy varnish
- Solid state Automatic Voltage Regulator
- Stator winding with 2/3 pitch for improved harmonics

### CONTROL SYSTEM

Control supervision and protection panel is mounted on the genset base frame. The control panel varies depending on requirement, in general Ignite Power generators are equipped with Deep Sea. The main features for Deep Sea are as follows:

#### KEY BENEFITS

- Hours counter provides accurate information for monitoring and maintenance periods
- User-friendly set-up and button layout for ease of use
- Multiple parameters are monitored simultaneously which are clearly displayed on a large back-lit icon display
- The module can be configured to suit a wide range of applications
- Compatible with a wide range of CAN engines, including tier 4 engine support
- Uses DSE Configuration Suite PC Software for simplified configuration
- Licence-free PC software
- IP65 rating (with optional gasket) offers increased resistance to water ingress

#### KEY FEATURES

- Large back-lit icon display
- Heated display option available
- Fully configurable via the fascia or PC using USB communication
- Efficient power save mode
- 3 phase generator sensing
- 3 phase mains (utility) sensing (DSE6620 only)
- Generator/load power monitoring (kW, kV A, kV Ar, pf)
- Generator overload protection
- Generator/load current monitoring and protection
- Breaker control via fascia buttons
- Fuel and start outputs (configurable when using CAN)
- 4 configurable DC outputs
- 4 configurable analogue/digital inputs
- 6 configurable digital inputs
- Configurable staged loading outputs

- CAN, MPU and alternator speed sensing in one variant
- 3 engine maintenance alarms
- Engine speed protection
- Engine hours counter
- Engine pre-heat
- Engine run-time scheduler
- Engine idle control for starting & stopping
- Fuel pump control
- Real time clock options available
- Battery voltage monitoring
- Start on low battery voltage
- Configurable remote start input
- 1 alternative configuration
- Comprehensive warning, electrical trip or shutdown protection upon fault condition
- LCD and LED alarm indication
- Configurable event log (50)



Also Gensets can be equipped with different control panels depending on usage such as:  
 DSE 6610: Basic Autostart operation with stand alone application  
 DSE 7310: advanced Autostart operation with high protections  
 DSE 7320: advanced auto mains failure operation with high protection  
 DSE 8610: for synchronization application/solution

### OPTIONAL EQUIPMENTS

#### Diesel Engine

- Oil heater

#### Alternator

- 3/4 Pole Output Circuit Breaker
- Anti - condensation Heater

#### Panel

- Charge ammeter
- Transfer Switch 3 Pole
- Transfer Switch 4 Pole
- Earth Fault, single set

#### Accessories

- Bulk fuel tank
- Automatic filling system
- Fuel - water separator filter
- Low fuel level alarm
- Residential silencer
- Enclosure or sound proof canopy
- Trailer
- Manual oil drain pump
- Tool kit for maintenance